

Radiance™

High Gloss 18 18% Floor Finish



DESCRIPTION

This product is a simplified floor finish that provides the end user with an extremely tough and durable high gloss finish. It is formulated to respond to low, high, and ultra high speed maintenance techniques and is self-sealing so fewer products are needed to complete the job.

DIRECTIONS

1. Strip floor entirely of old finish using one of our recommended floor strippers.
2. Apply finish using a clean finish mop or applicator. Apply 3 - 5 coats per application. Allow 30 - 45 minutes after each coat for finish to dry completely before recoating.
3. Maintain floor by dust mopping and damp mopping as needed.
4. Restore floor by damp mopping thoroughly with our recommended cleaner and buff or burnish using our recommended spray buff or mop on restorer.

IF USING PRODUCT ON CONCRETE, TERRAZZO, MARBLE, OR GRANITE: It is recommended that two coats of floor sealer be used to seal floor, followed by 2 - 5 coats of finish. Restore and maintain floor as normal.

RECOMMENDED PADS FOR BUFFING OR BURNISHING:

175 - 1500 RPM: Soft White or Red
1500+ RPM: White, Champagne, or Light Natural

KEEP FROM FREEZING

APPLICATIONS

Recommended for low maintenance areas where an economical finish is desired:

- Schools & hospitals
- Airports & offices

BENEFITS

- Economical and durable
- Excellent off-the-mop gloss
- Easy to maintain
- Will not yellow
- Recommended for occasional spray buffing or burnishing

SPECIFICATIONS

Color..... White
Fragrance Characteristic
pH Range..... 8.0 - 8.5
Dilution..... RTU
Density 8.55
% Non-volatile solids 18%
Coverage 2000 sq. ft./gal.

PACKAGING

ITEM # SIZE
10079816..... 5 gal.

