Radiance

High Gloss 22

22% Urethane Fortified Floor Finish



DESCRIPTION

This product is designed for heavy traffic areas such as supermarkets, retail, and institutional settings on all types of resilient flooring. Unique water based urethane emulsion gives a superior wet look gloss with superb detergent resistance and durability. Contains UFW^{TM} Technology to prevent discoloration and dirt penetration to stay looking clean longer, extending the period between stripping cycles.

DIRECTIONS

- 1. Strip floor entirely of old finish using one of our recommended floor strippers.
- 2. Apply finish using a clean finish mop or applicator. Apply 3 to 7 coats per application. Allow 30 45 minutes after each coat for finish to dry completely before recoating.
- 3. Allow at least 2 hours after final coat dries before burnishing (**NOTE:** It is always recommended to wait 24 hours before burnishing; however, this product can be burnished 2 hours after product dries).
- 4. Maintain floor by dust mopping and spot mopping as needed.
- 5. Auto scrub with our recommended floor cleaner using a red pad before burnishing.
- 6. Periodically deep scrub with our recommended floor cleaner and a blue pad before recoating.

FOR USE ON HARD SURFACES SUCH AS CONCRETE, TERRAZZO, MARBLE, OR GRANITE: It is recommended that two coats of sealer be applied to surface to seal floor properly. Follow with 3 - 5 coats of finish. Burnish and maintain as normal.

RECOMMENDED BURNISH PADS:

Americo Combo Lite, ETC Gorilla, Glit Joey Polish, Microtron White Polish, 3M White Polish, Triple S White.

KEEP FROM FREEZING

APPLICATIONS

Recommended for areas with daily maintenance desired:

- Contract cleaners
- Supermarkets
- Retail

BENEFITS

- Balances price with performance
- Durable
- Good off-the-mop gloss
- Easy to maintain

SPECIFICATIONS

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	860
% Non-volatile solids	22%
Coverage	2000 sq. ft./gal.

PACKAGING

ITEM #	SIZE
10142608	2.5 aal.



